

HB-2X2-RS

~10° spot beam

TECHNICAL SPECIFICATIONS:

Dimensions	50.0 x 50.0 mm
Height	10 mm
Fastening	screw
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
HB-2X2-RS	Multi-lens	PMMA	clear	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C14541_HB-2X2-RS » Box size: 480 x 280 x 300 mm	800	160	160	10.2






See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):





LED QUICK FLUX XTP 2x6 xxx LS G5
 FWHM / FWTM 14.0° / 29.0°
 Efficiency 94 %
 Peak intensity 9.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XD16
 FWHM / FWTM 11.0° / 23.0°
 Efficiency 93 %
 Peak intensity 13.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XHP35 HD
 FWHM / FWTM 24.0° / 42.0°
 Efficiency 89 %
 Peak intensity 4.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XM-L3
 FWHM / FWTM 20.0° / 36.0°
 Efficiency 96 %
 Peak intensity 6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (MEASURED):


CREE LED

LED XP-E2
FWHM / FWTM 10.0° / 18.0°
Efficiency 94 %
Peak intensity 22.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:




CREE LED

LED XP-G2
FWHM / FWTM 14.0° / 25.0°
Efficiency 94 %
Peak intensity 11.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




CREE LED

LED XP-L HI
FWHM / FWTM 13.0° / 25.0°
Efficiency 94 %
Peak intensity 11.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



CREE LED


LED XP-L2
FWHM / FWTM 21.0° / 43.0°
Efficiency 94 %
Peak intensity 4.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):




LED LUXEON V2
FWHM / FWTM 15.0° / 28.0°
Efficiency 94 %
Peak intensity 9.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED SST-10-B130
FWHM / FWTM 12.0° / 21.0°
Efficiency 96 %
Peak intensity 15.9 cd/lm
LEDs/each optic 1
Light colour Deep Red
Required components:



LED NVSW219D
FWHM / FWTM 17.0° / 29.0°
Efficiency 94 %
Peak intensity 8.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSW219F
FWHM / FWTM 17.0° / 29.0°
Efficiency 94 %
Peak intensity 8.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):




LED NVSW319B
FWHM / FWTM 18.0° / 32.0°
Efficiency 94 %
Peak intensity 7.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSW3x9A
FWHM / FWTM 19.0° / 33.0°
Efficiency 94 %
Peak intensity 6.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSxE21A
FWHM / FWTM 11.0° / 28.0°
Efficiency 89 %
Peak intensity 11.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSxx19B/NVSxx19C
FWHM / FWTM 17.0° / 30.0°
Efficiency 93 %
Peak intensity 8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):




LED NWSx229A
FWHM / FWTM 23.0° / 41.0°
Efficiency 94 %
Peak intensity 4.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OSRAM

LED PL-BRICK HP 3800 2x8 SSG
FWHM / FWTM 16.0° / 28.0°
Efficiency 95 %
Peak intensity 8.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM


LED PrevaLED Core Z3 LES9
FWHM / FWTM 13.5° / 26.0°
Efficiency 95 %
Peak intensity 11 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors


LED OSLON Square CSSRM2/CSSRM3
FWHM / FWTM 15.0° / 27.0°
Efficiency 90 %
Peak intensity 11 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



PHILIPS

LED Fortimo FastFlex LED 2x8 DA G4
 FWHM / FWTM 13.0° / 23.0°
 Efficiency 93 %
 Peak intensity 12.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




PHILIPS

LED Fortimo FastFlex LED 2x8 DA G4+
 FWHM / FWTM 17.0° / 32.0°
 Efficiency 96 %
 Peak intensity 7.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




PHILIPS

LED Fortimo FastFlex LED 2x8 DA G5
 FWHM / FWTM 14.0° / 27.0°
 Efficiency 96 %
 Peak intensity 10.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG


LED HiLOM RC12 Z (LH181B)
 FWHM / FWTM 12.0° / 33.0°
 Efficiency 97 %
 Peak intensity 9.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (MEASURED):


SAMSUNG

LED HiLOM RH12 Z (LH351C)
 FWHM / FWTM 17.0° / 29.0°
 Efficiency 96 %
 Peak intensity 8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED HiLOM RH16 (LH351C)
 FWHM / FWTM 17.0° / 30.0°
 Efficiency 94 %
 Peak intensity 8.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LH351B
 FWHM / FWTM 17.0° / 29.0°
 Efficiency 89 %
 Peak intensity 8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG



LED LH351C
 FWHM / FWTM 18.0° / 30.0°
 Efficiency 94 %
 Peak intensity 7.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (MEASURED):


SAMSUNG

LED LH351D
FWHM / FWTM 22.0° / 38.0°
Efficiency 94 %
Peak intensity 4.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SKITEC

LED LED-Pa-L15c2W11c2-xxx-C050-01
FWHM / FWTM 14.0° / 27.0°
Efficiency 96 %
Peak intensity 10.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SEOL

SEOUL SEMICONDUCTOR
LED Z5M3
FWHM / FWTM 16.0° / 31.0°
Efficiency 94 %
Peak intensity 7.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SEOL

SEOUL SEMICONDUCTOR
LED Z5M4
FWHM / FWTM 17.0° / 32.0°
Efficiency 96 %
Peak intensity 7.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):

SEOUL SEMICONDUCTOR LED Z8Y22 FWHM / FWTM 14.0° / 35.0° Efficiency 94 % Peak intensity 6.6 cd/lm LEDs/each optic 1 Light colour White Required components:		
SEOUL SEMICONDUCTOR LED Z8Y22P FWHM / FWTM 16.0° / 33.0° Efficiency 93 % Peak intensity 6.9 cd/lm LEDs/each optic 1 Light colour White Required components:		
TRIDONIC LED RLE 2x4 2000lm HP EXC2 OTD FWHM / FWTM 13.0° / 25.0° Efficiency 94 % Peak intensity 12.5 cd/lm LEDs/each optic 1 Light colour White Required components:		
TRIDONIC LED RLE 2x8 4000lm HP EXC2 OTD FWHM / FWTM 13.0° / 25.0° Efficiency 94 % Peak intensity 12.5 cd/lm LEDs/each optic 1 Light colour White Required components:		

PHOTOMETRIC DATA (MEASURED):


TRIDONIC

LED RLE G1 49x121mm 2000lm xxx EXC OTD
 FWHM / FWTM 13.0° / 27.0°
 Efficiency 94 %
 Peak intensity 10.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





TRIDONIC

LED RLE G1 49x133mm 2000lm xxx EXC OTD
 FWHM / FWTM 13.0° / 27.0°
 Efficiency 94 %
 Peak intensity 10.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





TRIDONIC

LED RLE G1 49x223mm 4000lm xxx EXC OTD
 FWHM / FWTM 13.0° / 27.0°
 Efficiency 94 %
 Peak intensity 10.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



TRIDONIC


LED RLE G1 49x245mm 4000lm xxx EXC OTD
 FWHM / FWTM 13.0° / 27.0°
 Efficiency 94 %
 Peak intensity 10.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XHP35 HI
FWHM / FWTM 14.0° / 29.0°
Efficiency 93 %
Peak intensity 9.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XHP35.2 HD
FWHM / FWTM 24.0° / 46.0°
Efficiency 93 %
Peak intensity 3.6 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XM-L
FWHM / FWTM 19.0° / 38.0°
Efficiency 92 %
Peak intensity 5.6 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XM-L2
FWHM / FWTM 18.0° / 34.0°
Efficiency 94 %
Peak intensity 6.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):



LED XP-E2
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 95 %
 Peak intensity 14.4 cd/lm
 LEDs/each optic 1
 Light colour Red
 Required components:




LED XP-G
 FWHM / FWTM 13.0° / 27.0°
 Efficiency 93 %
 Peak intensity 12.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XP-G2
 FWHM / FWTM 14.0° / 26.0°
 Efficiency 89 %
 Peak intensity 11 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:

Protective plate, glass




LED XP-G2 HE
 FWHM / FWTM 16.0° / 34.0°
 Efficiency 94 %
 Peak intensity 7.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (SIMULATED):




LED XP-G3
 FWHM / FWTM 16.0° / 33.0°
 Efficiency 94 %
 Peak intensity 7.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XP-L HD
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 90 %
 Peak intensity 6.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:

Protective plate, glass




LED XP-L HD
 FWHM / FWTM 19.0° / 35.0°
 Efficiency 94 %
 Peak intensity 6.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XP-L HI
 FWHM / FWTM 13.0° / 25.0°
 Efficiency 89 %
 Peak intensity 10.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:

Protective plate, glass




PHOTOMETRIC DATA (SIMULATED):




LED XP-L2
 FWHM / FWTM 20.0° / 40.0°
 Efficiency 89 %
 Peak intensity 4.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:


Protective plate, glass




LED XP-P
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 95 %
 Peak intensity 25.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XQ-E HI
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 94 %
 Peak intensity 28.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED LUXEON C
 FWHM / FWTM 11.0° / 24.0°
 Efficiency 94 %
 Peak intensity 16.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (SIMULATED):


LUMILEDS

LED LUXEON CZ
FWHM / FWTM 8.0° / 16.0°
Efficiency 93 %
Peak intensity 29.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON HL2X
FWHM / FWTM 14.0° / 30.0°
Efficiency 95 %
Peak intensity 9 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON IR Domed 150
FWHM / FWTM 11.0° / 21.0°
Efficiency 94 %
Peak intensity 19.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LUMILEDS

LED LUXEON IR Domed 60
FWHM / FWTM 10.0° / 20.0°
Efficiency 93 %
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):

OSRAM

Opto Semiconductors


LED OSCONIQ C 2424
FWHM / FWTM 10.0° / 20.0 + 21.0°
Efficiency 96 %
Peak intensity 18 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors

LED OSCONIQ P 3030
FWHM / FWTM 8.0° / 20.0°
Efficiency 95 %
Peak intensity 22.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OSRAM

Opto Semiconductors

LED OSCONIQ P 3737 (2W version)
FWHM / FWTM 12.0° / 24.0°
Efficiency 90 %
Peak intensity 12.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:


Protective plate, glass



OSRAM

Opto Semiconductors

LED OSCONIQ P 3737 (2W version)
FWHM / FWTM 12.0° / 24.0°
Efficiency 95 %
Peak intensity 13.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):

OSRAM

Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3
FWHM / FWTM 15.0° / 27.0°
Efficiency 81 %
Peak intensity 9.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:


Protective plate, glass



OSRAM

Opto Semiconductors


LED OSLON Square Flat
FWHM / FWTM 10.0° / 20.0°
Efficiency 96 %
Peak intensity 19.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors


LED OSLON SSL 80
FWHM / FWTM 8.2° / 18.8°
Efficiency 94 %
Peak intensity 21 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors

LED OSTAR Projection Compact (Kx.CSLNM1.xx)
FWHM / FWTM 10.0° / 20.0°
Efficiency 96 %
Peak intensity 19.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):

OSRAM


Opto Semiconductors

LED SFH 4715AS
 FWHM / FWTM 9.2° / 21.0°
 Efficiency %
 LEDs/each optic 1
 Light colour IR
 Required components:




SAMSUNG

LED LH231B
 FWHM / FWTM 16.0° / 34.0°
 Efficiency 94 %
 Peak intensity 8 cd/lm
 LEDs/each optic 4
 Light colour White
 Required components:




SAMSUNG

LED LH231B
 FWHM / FWTM 16.0° / 32.0°
 Efficiency 95 %
 Peak intensity 8.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG


LED LH231B
 FWHM / FWTM 16.0° / 32.0°
 Efficiency 95 %
 Peak intensity 8.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED LM301B
FWHM / FWTM 10.0° / 24.0°
Efficiency 94 %
Peak intensity 14.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2
FWHM / FWTM 13.0° / 26.0°
Efficiency 92 %
Peak intensity 12.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR

LED Z8Y22T
FWHM / FWTM 15.0° / 32.0°
Efficiency 94 %
Peak intensity 8.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)