

TUIJA-3-SS

~12° smooth spot beam

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 50.0 mm
Height	14.5 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
TUIJA-3-SS	Multi-lens	PMMA	clear	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C11192_TUIJA-3-SS » Box size: 480 x 280 x 300 mm	364	112	28	6.6






See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):



LED XB-D
FWHM / FWTM 14.0° / 32.0°
Efficiency 94 %
Peak intensity 7.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XB-D
FWHM / FWTM 14.0° / 32.0°
Efficiency 94 %
Peak intensity 7.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-E
FWHM / FWTM 12.0° / 25.0°
Efficiency 90 %
Peak intensity 14.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-G
FWHM / FWTM 14.0° / 29.0°
Efficiency 90 %
Peak intensity 9.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LED XT-E
FWHM / FWTM 13.0° / 30.0°
Efficiency 94 %
Peak intensity 11 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON A
FWHM / FWTM 12.0°
Efficiency 90 %
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON Rebel
FWHM / FWTM 12.0° / 22.0°
Efficiency 90 %
Peak intensity 16.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON Rebel ES
FWHM / FWTM 13.0° / 27.0°
Efficiency 90 %
Peak intensity 11.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:

PHOTOMETRIC DATA (MEASURED):



LED NCSxx19A
FWHM / FWTM 12.0°
Efficiency 90 %
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19A
FWHM / FWTM 10.5°
Efficiency 90 %
LEDs/each optic 1
Light colour White
Required components:




Opto Semiconductors

LED OSOLON SSL 80
FWHM / FWTM 10.0° / 21.0°
Efficiency 90 %
Peak intensity 4.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR

LED Z5
FWHM / FWTM 10.0° / 22.0°
Efficiency 93 %
Peak intensity 22 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):


SHARP

LED	Double Dome (GM2BB)
FWHM / FWTM	12.0°
Efficiency	90 %
LEDs/each optic	1
Light colour	White
Required components:	


PHOTOMETRIC DATA (SIMULATED):




LED XD16
FWHM / FWTM 9.5° / 18.0°
Efficiency 94 %
Peak intensity 27.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XP-L HD
FWHM / FWTM 12.0° / 24.0°
Efficiency 97 %
Peak intensity 16.7 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XP-L HI
FWHM / FWTM 12.0° / 22.0°
Efficiency 97 %
Peak intensity 18.6 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XP-L2
FWHM / FWTM 12.0° / 26.0°
Efficiency 97 %
Peak intensity 13.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED LUXEON Rebel Plus
FWHM / FWTM 10.0° / 21.0°
Efficiency 96 %
Peak intensity 20.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSCONIQ P 3737 (3W version)
FWHM / FWTM 11.0° / 22.0°
Efficiency 97 %
Peak intensity 19 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSLON Square CSSRM2/CSSRM3
FWHM / FWTM 11.0° / 20.0°
Efficiency 94 %
Peak intensity 23.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED OSLON SSL 150
FWHM / FWTM 12.0°
Efficiency %
Peak intensity 17 cd/lm
LEDs/each optic 1
Light colour White
Required components:

PHOTOMETRIC DATA (SIMULATED):

OSRAM

Opto Semiconductors


LED SFH 4715AS
FWHM / FWTM 12.0° / 24.0°
Efficiency 94 %
Peak intensity 17.1 cd/lm
LEDs/each optic 1
Light colour IR
Required components:



OSRAM


Opto Semiconductors

LED SFH 4716AS
FWHM / FWTM 12.0° / 24.0°
Efficiency 94 %
Peak intensity 17.1 cd/lm
LEDs/each optic 1
Light colour IR
Required components:



SAMSUNG

LED LH351D
FWHM / FWTM 12.0° / 26.0°
Efficiency 96 %
Peak intensity 14.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)