



**WINSTAR Display Co.,Ltd.**  
**華凌光電股份有限公司**

## SPECIFICATION

**CUSTOMER :** \_\_\_\_\_

**MODULE NO.:** **WO24064C-TFH#**

|                                                  |                     |              |
|--------------------------------------------------|---------------------|--------------|
| <b>APPROVED BY:</b><br>( FOR CUSTOMER USE ONLY ) | <b>PCB VERSION:</b> | <b>DATA:</b> |
|--------------------------------------------------|---------------------|--------------|

| SALES BY | APPROVED BY | CHECKED BY | PREPARED BY |
|----------|-------------|------------|-------------|
|          |             |            |             |

| VERSION | DATE       | REVISED<br>PAGE NO. | SUMMARY     |
|---------|------------|---------------------|-------------|
| F       | 2017/09/05 |                     | Modify Idd. |

**RECORDS OF REVISION****DOC. FIRST ISSUE**

| VERSION | DATE       | REVISED<br>PAGE NO. | SUMMARY                                                                  |
|---------|------------|---------------------|--------------------------------------------------------------------------|
| 0       | 2014/01/24 |                     | First issue                                                              |
| A       | 2015/02/02 |                     | Add Pull tape.                                                           |
| B       | 2016/01/07 |                     | Modify Response Time                                                     |
| C       | 2016/01/27 |                     | Modify Precautions in use<br>of LCD Modules<br>& Static electricity test |
| D       | 2016/11/21 |                     | Add FPC bending rule                                                     |
| E       | 2017/03/10 |                     | Modify Backlight<br>Information                                          |
| F       | 2017/09/05 |                     | Modify Idd.                                                              |

# Contents

- 1.Module Classification Information
- 2.Precautions in use of LCD Modules
- 3.General Specification
- 4.Absolute Maximum Ratings
- 5.Electrical Characteristics
- 6.Optical Characteristics
- 7.Interface Pin Function
- 8.Contour Drawing &Block Diagram
- 9.Reliability
- 10.Backlight Information
- 11.Inspection specification
- 12.Material List of Components for RoHs
- 13.Recommendable Storage
- 14.Other

# 1.Module Classification Information

W      O      24064      C      —      T      F      H      —      #  
 ①      ②      ③      ④           ⑤      ⑥      ⑦           ⑧

① Brand : WINSTAR DISPLAY CORPORATION

② Display Type : H→Character Type, G→Graphic Type , X→TAB Type, O→COG Type

③ Display Font : 240 \* 64 dot

④ Model serials no.

⑤ Backlight Type :

|                     |                   |                         |
|---------------------|-------------------|-------------------------|
| N→Without backlight | T→LED, White      | S→LED, High light White |
| B→EL, Blue green    | A→LED, Amber      | L→LED, Full color       |
| D→EL, Green         | R→LED, Red        | J→DIP LED,Blue          |
| W→EL, White         | O→LED, Orange     | K→DIP LED,White         |
| M→EL, Yellow Green  | G→LED, Green      | E→DIP LED, Yellow Green |
| F→CCFL, White       | P→LED, Blue       | H→DIP LED,Amber         |
| Y→LED, Yellow Green | X→LED, Dual color | I→DIP LED, Red          |
| G→LED, Green        | C→LED, Full color |                         |

⑥ LCD Mode :

|                              |                               |
|------------------------------|-------------------------------|
| B→TN Positive, Gray          | V→FSTN Negative, Blue         |
| N→TN Negative,               | T→FSTN Negative, Black        |
| L→VA Negative                | D→FSTN Negative (Double film) |
| H→ HTN Positive, Gray        | F→FSTN Positive               |
| I→HTN Negative, Black        | K→FSC Negative                |
| U→HTN Negative, Blue         | S→FSC Positive                |
| M→STN Negative, Blue         | E→ISTN Negative, Black        |
| G→STN Positive, Gray         | C→CSTN Negative, Black        |
| Y→STN Positive, Yellow Green | A→ASTN Negative, Black        |


⑦ LCD Polarize

|                            |                            |
|----------------------------|----------------------------|
| A→Reflective, N.T, 6:00    | H→Transflective, W.T,6:00  |
| D→Reflective, N.T, 12:00   | K→Transflective, W.T,12:00 |
| G→Reflective, W. T, 6:00   | C→Transmissive, N.T,6:00   |
| J→Reflective, W. T, 12:00  | F→Transmissive, N.T,12:00  |
| B→Transflective, N.T,6:00  | I→Transmissive, W. T, 6:00 |
| E→Transflective, N.T,12:00 | L→Transmissive, W.T,12:00  |

⑧ Special Code      # : Fit in with the ROHS Directions and regulations

## **2.Precautions in use of LCD Modules**

- (1) Avoid applying excessive shocks to the module or making any alterations or modifications to it.
- (2) Don't make extra holes on the printed circuit board, modify its shape or change the components of LCD module.
- (3) Don't disassemble the LCM.
- (4) Don't operate it above the absolute maximum rating.
- (5) Don't drop, bend or twist LCM.
- (6) Soldering: only to the I/O terminals.
- (7) Storage: please storage in anti-static electricity container and clean environment.
- (8) Winstar have the right to change the passive components, including R3,R6 & backlight adjust resistors. (Resistors, capacitors and other passive components will have different appearance and color caused by the different supplier.)
- (9) Winstar have the right to change the PCB Rev. (In order to satisfy the supplying stability, management optimization and the best product performance...etc, under the premise of not affecting the electrical characteristics and external dimensions, Winstar have the right to modify the version.)
- (10) To ensure the stability of the display screen, please apply screen saver after showing 30 mins of fixed display content.
- (11) The limitation of FPC bending



### **3.General Specification**

| Item             | Dimension                                                                                                                                            | Unit |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Number of dots   | 240 x 64                                                                                                                                             | —    |
| Module dimension | 111.4 x 45.5 x 5.6                                                                                                                                   | mm   |
| View area        | 106.2 x 31.2                                                                                                                                         | mm   |
| Active area      | 103.17 x 27.49                                                                                                                                       | mm   |
| Dot size         | 0.40 x 0.40                                                                                                                                          | mm   |
| Dot pitch        | 0.43 x 0.43                                                                                                                                          | mm   |
| LCD type         | FSTN Transflective Positive<br>(In LCD production, It will occur slightly color difference. We can only guarantee the same color in the same batch.) |      |
| Duty             | 1/64                                                                                                                                                 |      |
| View direction   | 6 o'clock                                                                                                                                            |      |
| Backlight Type   | LED, White                                                                                                                                           |      |
| IC               | ST7586S                                                                                                                                              |      |

## **4.Absolute Maximum Ratings**

| Item                         | Symbol          | Min  | Typ | Max | Unit |
|------------------------------|-----------------|------|-----|-----|------|
| Operating Temperature        | T <sub>OP</sub> | -20  | —   | +70 | °C   |
| Storage Temperature          | T <sub>ST</sub> | -30  | —   | +80 | °C   |
| Digital Power Supply Voltage | VDDI            | -0.3 | —   | 3.6 | V    |
| Analog Power supply voltage  | VDDA            | -0.3 | —   | 3.6 | V    |
| LCD Power supply voltage     | V0-XV0          | -0.3 | —   | 19  | V    |
| LCD Power supply voltage     | VG              | -0.3 | —   | 5.5 | V    |

## 5. Electrical Characteristics



| Item                                     | Symbol          | Condition                 | Min         | Typ  | Max         | Unit |
|------------------------------------------|-----------------|---------------------------|-------------|------|-------------|------|
| Supply Voltage For Logic                 | $V_{DD}-V_{SS}$ | —                         | 3.0         | 3.3  | 3.4         | V    |
| Supply Voltage For LCM                   | $V_0-XV_0$      | $T_a=-20^{\circ}\text{C}$ | —           | —    | —           | V    |
|                                          |                 | $T_a=25^{\circ}\text{C}$  | 9.8         | 10.0 | 10.2        | V    |
|                                          |                 | $T_a=+70^{\circ}\text{C}$ | —           | —    | —           | V    |
| Input High Volt.                         | $V_{IH}$        | —                         | $0.7V_{DD}$ | —    | $V_{DD}$    | V    |
| Input Low Volt.                          | $V_{IL}$        | —                         | $V_{SS}$    | —    | $0.3V_{DD}$ | V    |
| Output High Volt.                        | $V_{OH}$        | —                         | $0.8V_{DD}$ | —    | $V_{DD}$    | V    |
| Output Low Volt.                         | $V_{OL}$        | —                         | $V_{SS}$    | —    | $0.2V_{DD}$ | V    |
| Supply Current(No include LED Backlight) | $I_{DD}$        | $V_{DD}=3.3\text{V}$      | 0.1         | 1.5  | 3.0         | mA   |

Please kindly consider to design the  $V_{op}$  to be adjustable while programing the software to match LCD contrast tolerance.



## 6.Optical Characteristics

| Item           | Symbol   | Condition   | Min | Typ | Max | Unit               |
|----------------|----------|-------------|-----|-----|-----|--------------------|
| View Angle     | $\theta$ | $CR \geq 2$ | 0   | —   | 30  | $\phi = 180^\circ$ |
|                | $\theta$ | $CR \geq 2$ | 0   | —   | 60  | $\phi = 0^\circ$   |
|                | $\theta$ | $CR \geq 2$ | 0   | —   | 45  | $\phi = 90^\circ$  |
|                | $\theta$ | $CR \geq 2$ | 0   | —   | 45  | $\phi = 270^\circ$ |
| Contrast Ratio | CR       | —           | —   | 5   | —   | —                  |
| Response Time  | T rise   | —           | —   | 200 | 300 | ms                 |
|                | T fall   | —           | —   | 250 | 350 | ms                 |

### Definition of Operation Voltage (Vop)



### Definition of Response Time (Tr, Tf)



### Conditions :


Operating Voltage : Vop

Frame Frequency : 64 HZ

Viewing Angle( $\theta$  ,  $\phi$ ) :  $0^\circ$  ,  $0^\circ$

Driving Waveform : 1/N duty , 1/a bias

### Definition of viewing angle( $CR \geq 2$ )




## 7.Interface Pin Function


| Pin No.                                                        | Symbol | I/O   | Description                                                                                                                                                                                                                                                                         |     |                       |                          |
|----------------------------------------------------------------|--------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----------------------|--------------------------|
| 1                                                              | VG     | P     | VG is the power of SEG-drivers.                                                                                                                                                                                                                                                     |     |                       |                          |
| 2                                                              | XV0    | P     | Negative operating voltage of COM-drivers.                                                                                                                                                                                                                                          |     |                       |                          |
| 3                                                              | V0     | P     | Positive operating voltage of COM-drivers.<br>V0O is the output of the positive Vop generator.<br>V0I is the positive Vop supply of LCD drivers.<br>V0S is the sensor of the positive Vop generator.<br>V0O, V0I & V0S should be separated on ITO and be connected together by FPC. |     |                       |                          |
| 4                                                              | VM     | P     | VM is the non-select voltage level of COM-drivers.                                                                                                                                                                                                                                  |     |                       |                          |
| 5                                                              | VDDA   | P     | Analog power for internal booster.                                                                                                                                                                                                                                                  |     |                       |                          |
| 6                                                              | VSS    | P     | Ground                                                                                                                                                                                                                                                                              |     |                       |                          |
| 7                                                              | VD1    | P     | VD1I is the power source of digital circuits.                                                                                                                                                                                                                                       |     |                       |                          |
| 8                                                              | VDDI   | P     | Power of interface I/O circuit.                                                                                                                                                                                                                                                     |     |                       |                          |
| 9                                                              | CSB    | Input | Chip select input pin.<br>CSB="L": This chip is selected and the MPU interface is active.                                                                                                                                                                                           |     |                       |                          |
| 10                                                             | IF3    | Input | These pins select interface operation mode.                                                                                                                                                                                                                                         |     |                       |                          |
| 11                                                             | IF2    |       | IF3                                                                                                                                                                                                                                                                                 | IF2 | IF1                   | MPU interface type       |
|                                                                |        |       | H                                                                                                                                                                                                                                                                                   | H   | L                     | 80 series 8-bit parallel |
|                                                                |        |       | H                                                                                                                                                                                                                                                                                   | L   | L                     | 68 series 8-bit parallel |
| 12                                                             | IF1    |       | L                                                                                                                                                                                                                                                                                   | H   | H                     | 8-bit serial (4-Line)    |
|                                                                |        | L     | H                                                                                                                                                                                                                                                                                   | L   | 9-bit serial (3-Line) |                          |
| Note: Refer to "Interface Selection" for detailed information. |        |       |                                                                                                                                                                                                                                                                                     |     |                       |                          |
| 13                                                             | RSTB   | Input | Reset input pin. When RSTB is "L", internal initialization procedure is executed.                                                                                                                                                                                                   |     |                       |                          |
| 14                                                             | /RD(E) | Input | Read / Write execution control pin. (This pin is only used in parallel interface)                                                                                                                                                                                                   |     |                       |                          |

|    |          |       |                                                                                                                                                                                                                                               |
|----|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 15 | D7       | I/O   | <p>The bi-directional data bus of the MPU interface. When CSB is “H”, they are high impedance.</p> <p>If using serial interface:<br/> D0 is the SDA signal in 4-Line &amp; 3-Line interface.<br/> D1 is the A0 signal in 4-Line interface</p> |
| 16 | D6       |       |                                                                                                                                                                                                                                               |
| 17 | D5       |       |                                                                                                                                                                                                                                               |
| 18 | D4       |       |                                                                                                                                                                                                                                               |
| 19 | D3       |       |                                                                                                                                                                                                                                               |
| 20 | D2       |       |                                                                                                                                                                                                                                               |
| 21 | D1       |       |                                                                                                                                                                                                                                               |
| 22 | D0       |       |                                                                                                                                                                                                                                               |
| 23 | NC       |       | No connection                                                                                                                                                                                                                                 |
| 24 | /WR(R/W) | Input | Read / Write execution control pin. (This pin is only used in parallel interface)                                                                                                                                                             |
| 25 | A0(SCL)  | Input | The function of this pin is different in parallel and serial interface.<br>In parallel interface: A0 is register selection input.                                                                                                             |
| 26 | VSS      | P     | Ground                                                                                                                                                                                                                                        |

## 8. Contour Drawing



## Application schematic



# 9. Reliability

Content of Reliability Test (Wide temperature, -20℃~70℃)

| Environmental Test                |                                                                                                                                                                                                                                                         |                                                                                                                                     |        |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|--------|
| Test Item                         | Content of Test                                                                                                                                                                                                                                         | Test Condition                                                                                                                      | Note   |
| High Temperature storage          | Endurance test applying the high storage temperature for a long time.                                                                                                                                                                                   | 80℃<br>200hrs                                                                                                                       | 2      |
| Low Temperature storage           | Endurance test applying the low storage temperature for a long time.                                                                                                                                                                                    | -30℃<br>200hrs                                                                                                                      | 1,2    |
| High Temperature Operation        | Endurance test applying the electric stress (Voltage & Current) and the thermal stress to the element for a long time.                                                                                                                                  | 70℃<br>200hrs                                                                                                                       | —<br>— |
| Low Temperature Operation         | Endurance test applying the electric stress under low temperature for a long time.                                                                                                                                                                      | -20℃<br>200hrs                                                                                                                      | 1      |
| High Temperature/Humidity storage | The module should be allowed to stand at 60℃,90%RH max<br>For 96hrs under no-load condition excluding the polarizer, Then taking it out and drying it at normal temperature.                                                                            | 60℃,90%RH<br>96hrs                                                                                                                  | 1,2    |
| Thermal shock resistance          | The sample should be allowed stand the following 10 cycles of operation<br><div style="text-align: center;"> <p style="margin: 0;">-20℃      25℃      70℃</p> <p style="margin: 0;">30min    5min    30min</p> <p style="margin: 0;">1 cycle</p> </div> | -20℃/70℃<br>10 cycles                                                                                                               | —<br>— |
| Vibration test                    | Endurance test applying the vibration during transportation and using.                                                                                                                                                                                  | Total fixed amplitude : 1.5mm<br>Vibration Frequency : 10~55Hz<br>One cycle 60 seconds to 3 directions of X,Y,Z for Each 15 minutes | 3      |
| Static electricity test           | Endurance test applying the electric stress to the terminal.                                                                                                                                                                                            | VS=±600V(contact),<br>±800v(air),<br>RS=330Ω<br>CS=150pF<br>10 times                                                                | —<br>— |

**Note1: No dew condensation to be observed.**

**Note2: The function test shall be conducted after 4 hours storage at the normal Temperature and humidity after remove from the test chamber.**

**Note3: The packing have to including into the vibration testing.**

# 10.Backlight Information

## Specification



| PARAMETER                             | SYMBOL           | MIN  | TYP  | MAX  | UNIT              | TEST CONDITION                                          |
|---------------------------------------|------------------|------|------|------|-------------------|---------------------------------------------------------|
| Supply Current                        | I <sub>LED</sub> | 40   | 120  | 160  | mA                | V= 3.5 V(Note 1)                                        |
| Supply Voltage                        | V                | 3.3  | 3.5  | 3.7  | V                 | —                                                       |
| Reverse Voltage                       | V <sub>R</sub>   | —    | —    | 5    | V                 | —                                                       |
| Color coordinate                      | X                | 0.26 | 0.29 | 0.32 | —                 | —                                                       |
|                                       | Y                | 0.27 | 0.30 | 0.33 | —                 | —                                                       |
| Luminance<br>(Without LCD)            | I <sub>V</sub>   | 800  | 1000 | —    | CD/M <sup>2</sup> | I <sub>LED</sub> = 120 mA                               |
| LED Life Time<br>(For Reference only) | —                | —    | 50K  | —    | Hr.               | I <sub>LED</sub> = 120 mA<br>25°C,50-60%RH,<br>(Note 2) |
| Color                                 | White            |      |      |      |                   |                                                         |

**Note:** The LED of B/L is drive by current only, drive voltage is for reference only.  
drive voltage can make driving current under safety area (current between minimum and maximum).

**Note 1:** Supply current minimum value is only for reference since LED brightness efficiency keeps enhancing. Current consumption becomes less and less to achieve the same luminance.



**Note 2:**50K hours is only an estimate for reference.




# 11. Inspection specification


| NO                      | Item                                                      | Criterion                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | AQL  |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
|-------------------------|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----------------|------------------|-----------------|-------------------------|---|-------------------------|---|---------------|---|--------|-------|-----------------|-----|---------------|-----------------|--------------|----------------------|---|--------------|----------------------|-----|------------|---------------|-----|
| 01                      | Electrical Testing                                        | Missing vertical, horizontal segment, segment contrast defect.<br>Missing character , dot or icon.<br>Display malfunction.<br>No function or no display.<br>Current consumption exceeds product specifications.<br>LCD viewing angle defect.<br>Mixed product types.<br>Contrast defect.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0.65 |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| 02                      | Black or white spots on LCD (display only)                | 2.1 White and black spots on display $\leq 0.25\text{mm}$ , no more than three white or black spots present.<br>2.2 Densely spaced: No more than two spots or lines within 3mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2.5  |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| 03                      | LCD black spots, white spots, contamination (non-display) | <div>3.1 Round type : As following drawing</div> <div><math>\Phi = (x + y) / 2</math></div> <div><table><tr><th>SIZE</th><th>Acceptable Q TY</th></tr><tr><td><math>\Phi \leq 0.10</math></td><td>Accept no dense</td></tr><tr><td><math>0.10 &lt; \Phi \leq 0.20</math></td><td>2</td></tr><tr><td><math>0.20 &lt; \Phi \leq 0.25</math></td><td>1</td></tr><tr><td><math>0.25 &lt; \Phi</math></td><td>0</td></tr></table></div> <div></div> <div>3.2 Line type : (As following drawing)</div> <div><table><tr><th>Length</th><th>Width</th><th>Acceptable Q TY</th></tr><tr><td>---</td><td><math>W \leq 0.02</math></td><td>Accept no dense</td></tr><tr><td><math>L \leq 3.0</math></td><td><math>0.02 &lt; W \leq 0.03</math></td><td rowspan="2">2</td></tr><tr><td><math>L \leq 2.5</math></td><td><math>0.03 &lt; W \leq 0.05</math></td></tr><tr><td>---</td><td><math>0.05 &lt; W</math></td><td>As round type</td></tr></table></div> <div></div> | SIZE | Acceptable Q TY | $\Phi \leq 0.10$ | Accept no dense | $0.10 < \Phi \leq 0.20$ | 2 | $0.20 < \Phi \leq 0.25$ | 1 | $0.25 < \Phi$ | 0 | Length | Width | Acceptable Q TY | --- | $W \leq 0.02$ | Accept no dense | $L \leq 3.0$ | $0.02 < W \leq 0.03$ | 2 | $L \leq 2.5$ | $0.03 < W \leq 0.05$ | --- | $0.05 < W$ | As round type | 2.5 |
| SIZE                    | Acceptable Q TY                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| $\Phi \leq 0.10$        | Accept no dense                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| $0.10 < \Phi \leq 0.20$ | 2                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| $0.20 < \Phi \leq 0.25$ | 1                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| $0.25 < \Phi$           | 0                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| Length                  | Width                                                     | Acceptable Q TY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| ---                     | $W \leq 0.02$                                             | Accept no dense                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| $L \leq 3.0$            | $0.02 < W \leq 0.03$                                      | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| $L \leq 2.5$            | $0.03 < W \leq 0.05$                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |
| ---                     | $0.05 < W$                                                | As round type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |      |                 |                  |                 |                         |   |                         |   |               |   |        |       |                 |     |               |                 |              |                      |   |              |                      |     |            |               |     |

|    |                      |                                                                                                                               |                         |                 |     |
|----|----------------------|-------------------------------------------------------------------------------------------------------------------------------|-------------------------|-----------------|-----|
| 04 | Polarizer<br>bubbles | If bubbles are visible,<br>judge using black spot<br>specifications, not easy<br>to find, must check in<br>specify direction. | Size $\Phi$             | Acceptable Q TY | 2.5 |
|    |                      |                                                                                                                               | $\Phi \leq 0.20$        | Accept no dense |     |
|    |                      |                                                                                                                               | $0.20 < \Phi \leq 0.50$ | 3               |     |
|    |                      |                                                                                                                               | $0.50 < \Phi \leq 1.00$ | 2               |     |
|    |                      |                                                                                                                               | $1.00 < \Phi$           | 0               |     |
|    |                      |                                                                                                                               | Total Q TY              | 3               |     |

WINSTAR DISPLAY Co., Ltd.

| NO                 | Item                  | Criterion                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | AQL               |                |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
|--------------------|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|----------------|----------------|---------------|-----------------------|---------------|--------------------|-----------------|---------------|-------------------|---------------|----------------|---------------|-----------------------|---------------|--------------------|-----------------|---------------|-----|
| 05                 | Scratches             | Follow NO.3 LCD black spots, white spots, contamination                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                   |                |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| 06                 | Chipped glass         | <p>Symbols Define:</p> <p>x: Chip length                  y: Chip width                  z: Chip thickness</p> <p>k: Seal width                  t: Glass thickness          a: LCD side length</p> <p>L: Electrode pad length:</p> <p>6.1 General glass chip :</p> <p>6.1.1 Chip on panel surface and crack between panels:</p>  <table> <tr> <td>z: Chip thickness</td> <td>y: Chip width</td> <td>x: Chip length</td> </tr> <tr> <td><math>Z \leq 1/2t</math></td> <td>Not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> <tr> <td><math>1/2t &lt; z \leq 2t</math></td> <td>Not exceed 1/3k</td> <td><math>x \leq 1/8a</math></td> </tr> </table> <p>⊙ If there are 2 or more chips, x is total length of each chip.</p> <p>6.1.2 Corner crack:</p>  <table> <tr> <td>z: Chip thickness</td> <td>y: Chip width</td> <td>x: Chip length</td> </tr> <tr> <td><math>Z \leq 1/2t</math></td> <td>Not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> <tr> <td><math>1/2t &lt; z \leq 2t</math></td> <td>Not exceed 1/3k</td> <td><math>x \leq 1/8a</math></td> </tr> </table> <p>⊙ If there are 2 or more chips, x is the total length of each chip.</p> | z: Chip thickness | y: Chip width  | x: Chip length | $Z \leq 1/2t$ | Not over viewing area | $x \leq 1/8a$ | $1/2t < z \leq 2t$ | Not exceed 1/3k | $x \leq 1/8a$ | z: Chip thickness | y: Chip width | x: Chip length | $Z \leq 1/2t$ | Not over viewing area | $x \leq 1/8a$ | $1/2t < z \leq 2t$ | Not exceed 1/3k | $x \leq 1/8a$ | 2.5 |
|                    |                       | z: Chip thickness                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | y: Chip width     | x: Chip length |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $Z \leq 1/2t$      | Not over viewing area | $x \leq 1/8a$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                   |                |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $1/2t < z \leq 2t$ | Not exceed 1/3k       | $x \leq 1/8a$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                   |                |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| z: Chip thickness  | y: Chip width         | x: Chip length                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                   |                |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $Z \leq 1/2t$      | Not over viewing area | $x \leq 1/8a$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                   |                |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $1/2t < z \leq 2t$ | Not exceed 1/3k       | $x \leq 1/8a$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                   |                |                |               |                       |               |                    |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |

| NO                    | Item           | Criterion                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | AQL           |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
|-----------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------------|-------------------|-----------------------|---------------|----------------|---------------|----------------|-------------------|------------|---------------|----------------|----------|-----------|---------------|------------|-----|
| 06                    | Glass crack    | <div> <div> <p>Symbols :</p> <p>x: Chip length                      y: Chip width                      z: Chip thickness</p> <p>k: Seal width                      t: Glass thickness                      a: LCD side length</p> <p>L: Electrode pad length</p> <p>6.2 Protrusion over terminal :</p> <p>6.2.1 Chip on electrode pad :</p>  <table> <tr> <td>y: Chip width</td> <td>x: Chip length</td> <td>z: Chip thickness</td> </tr> <tr> <td><math>y \leq 0.5\text{mm}</math></td> <td><math>x \leq 1/8a</math></td> <td><math>0 &lt; z \leq t</math></td> </tr> </table> <p>6.2.2 Non-conductive portion:</p>  <table> <tr> <td>y: Chip width</td> <td>x: Chip length</td> <td>z: Chip thickness</td> </tr> <tr> <td><math>y \leq L</math></td> <td><math>x \leq 1/8a</math></td> <td><math>0 &lt; z \leq t</math></td> </tr> </table> <p>⊙ If the chipped area touches the ITO terminal, over 2/3 of the ITO must remain and be inspected according to electrode terminal specifications.</p> <p>⊙ If the product will be heat sealed by the customer, the alignment mark not be damaged.</p> <p>6.2.3 Substrate protuberance and internal crack.</p>  <table> <tr> <td>y: width</td> <td>x: length</td> </tr> <tr> <td><math>y \leq 1/3L</math></td> <td><math>x \leq a</math></td> </tr> </table> </div> </div> | y: Chip width | x: Chip length | z: Chip thickness | $y \leq 0.5\text{mm}$ | $x \leq 1/8a$ | $0 < z \leq t$ | y: Chip width | x: Chip length | z: Chip thickness | $y \leq L$ | $x \leq 1/8a$ | $0 < z \leq t$ | y: width | x: length | $y \leq 1/3L$ | $x \leq a$ | 2.5 |
| y: Chip width         | x: Chip length | z: Chip thickness                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| $y \leq 0.5\text{mm}$ | $x \leq 1/8a$  | $0 < z \leq t$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| y: Chip width         | x: Chip length | z: Chip thickness                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| $y \leq L$            | $x \leq 1/8a$  | $0 < z \leq t$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| y: width              | x: length      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| $y \leq 1/3L$         | $x \leq a$     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |

| NO | Item               | Criterion                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | AQL                                                            |
|----|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| 07 | Cracked glass      | The LCD with extensive crack is not acceptable.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 2.5                                                            |
| 08 | Backlight elements | 8.1 Illumination source flickers when lit.<br>8.2 Spots or scratched that appear when lit must be judged. Using LCD spot, lines and contamination standards.<br>8.3 Backlight doesn't light or color wrong.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0.65<br>2.5<br>0.65                                            |
| 09 | Bezel              | 9.1 Bezel may not have rust, be deformed or have fingerprints, stains or other contamination.<br>9.2 Bezel must comply with job specifications.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 2.5<br>0.65                                                    |
| 10 | PCB、COB            | 10.1 COB seal may not have pinholes larger than 0.2mm or contamination.<br>10.2 COB seal surface may not have pinholes through to the IC.<br>10.3 The height of the COB should not exceed the height indicated in the assembly diagram.<br>10.4 There may not be more than 2mm of sealant outside the seal area on the PCB. And there should be no more than three places.<br>10.5 No oxidation or contamination PCB terminals.<br>10.6 Parts on PCB must be the same as on the production characteristic chart. There should be no wrong parts, missing parts or excess parts.<br>10.7 The jumper on the PCB should conform to the product characteristic chart.<br>10.8 If solder gets on bezel tab pads, LED pad, zebra pad or screw hold pad, make sure it is smoothed down.<br>10.9 The Scraping testing standard for Copper Coating of PCB<br> $X * Y \leq 2\text{mm}^2$ | 2.5<br>2.5<br>0.65<br>2.5<br>2.5<br>0.65<br>0.65<br>2.5<br>2.5 |
| 11 | Soldering          | 11.1 No un-melted solder paste may be present on the PCB.<br>11.2 No cold solder joints, missing solder connections, oxidation or icicle.<br>11.3 No residue or solder balls on PCB.<br>11.4 No short circuits in components on PCB.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 2.5<br>2.5<br>2.5<br>0.65                                      |

| NO | Item               | Criterion                                                                                                                               | AQL  |
|----|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------|------|
| 12 | General appearance | 12.1 No oxidation, contamination, curves or, bends on interface Pin (OLB) of TCP.                                                       | 2.5  |
|    |                    | 12.2 No cracks on interface pin (OLB) of TCP.                                                                                           | 0.65 |
|    |                    | 12.3 No contamination, solder residue or solder balls on product.                                                                       | 2.5  |
|    |                    | 12.4 The IC on the TCP may not be damaged, circuits.                                                                                    | 2.5  |
|    |                    | 12.5 The uppermost edge of the protective strip on the interface pin must be present or look as if it cause the interface pin to sever. | 2.5  |
|    |                    | 12.6 The residual rosin or tin oil of soldering (component or chip component) is not burned into brown or black color.                  | 2.5  |
|    |                    | 12.7 Sealant on top of the ITO circuit has not hardened.                                                                                | 2.5  |
|    |                    | 12.8 Pin type must match type in specification sheet.                                                                                   | 0.65 |
|    |                    | 12.9 LCD pin loose or missing pins.                                                                                                     | 0.65 |
|    |                    | 12.10 Product packaging must the same as specified on packaging specification sheet.                                                    | 0.65 |
|    |                    | 12.11 Product dimension and structure must conform to product specification sheet.                                                      | 0.65 |
|    |                    | 12.12 Visual defect outside of VA is not considered to be rejection.                                                                    | 0.65 |

# **12. Material List of Components for RoHs**

1. WINSTAR Display Co., Ltd hereby declares that all of or part of products (with the mark “#”in code), including, but not limited to, the LCM, accessories or packages, manufactured and/or delivered to your company (including your subsidiaries and affiliated company) directly or indirectly by our company (including our subsidiaries or affiliated companies) do not intentionally contain any of the substances listed in all applicable EU directives and regulations, including the following substances.

Exhibit A : The Harmful Material List

| Material                                         | (Cd)    | (Pb)     | (Hg)     | (Cr6+)   | PBBs     | PBDEs    |
|--------------------------------------------------|---------|----------|----------|----------|----------|----------|
| Limited Value                                    | 100 ppm | 1000 ppm | 1000 ppm | 1000 ppm | 1000 ppm | 1000 ppm |
| Above limited value is set up according to RoHS. |         |          |          |          |          |          |

2.Process for RoHS requirement : **(only for RoHS inspection)**

(1) Use the Sn/Ag/Cu soldering surface ; the surface of Pb-free solder is rougher than we used before.

(2) Heat-resistance temp. :

Reflow : 250°C,30 seconds Max. ;

Connector soldering wave or hand soldering : 320°C, 10 seconds max.

(3) Temp. curve of reflow, max. Temp. : 235±5°C ;

Recommended customer's soldering temp. of connector : 280°C, 3 seconds.

## **13.Recommendable Storage**

1. Place the panel or module in the temperature  $25^{\circ}\text{C}\pm 5^{\circ}\text{C}$  and the humidity below 65% RH
2. Do not place the module near organics solvents or corrosive gases.
3. Do not crush, shake, or jolt the module.

WINSTAR DISPLAY Co., Ltd.



Module Number : \_\_\_\_\_

Page: 1

**1、Panel Specification :**

- |                            |                               |                                     |
|----------------------------|-------------------------------|-------------------------------------|
| 1. Panel Type :            | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 2. View Direction :        | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 3. Numbers of Dots :       | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 4. View Area :             | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 5. Active Area :           | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 6. Operating Temperature : | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 7. Storage Temperature :   | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 8. Others :                | _____                         |                                     |

**2、Mechanical Specification :**

- |                             |                               |                                     |
|-----------------------------|-------------------------------|-------------------------------------|
| 1. PCB Size :               | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 2. Frame Size :             | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 3. Material of Frame :      | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 4. Connector Position :     | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 5. Fix Hole Position :      | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 6. Backlight Position :     | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 7. Thickness of PCB :       | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 8. Height of Frame to PCB : | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 9. Height of Module :       | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 10. Others :                | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |

**3、Relative Hole Size :**

- |                             |                               |                                     |
|-----------------------------|-------------------------------|-------------------------------------|
| 1. Pitch of Connector :     | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 2. Hole size of Connector : | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 3. Mounting Hole size :     | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 4. Mounting Hole Type :     | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 5. Others :                 | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |

**4、Backlight Specification :**

- |                                                   |                               |                                     |
|---------------------------------------------------|-------------------------------|-------------------------------------|
| 1. B/L Type :                                     | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 2. B/L Color :                                    | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 3. B/L Driving Voltage (Reference for LED Type) : | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 4. B/L Driving Current :                          | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 5. Brightness of B/L :                            | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 6. B/L Solder Method :                            | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 7. Others :                                       | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |

&gt;&gt; Go to page 2 &lt;&lt;

Module Number : \_\_\_\_\_

Page: 2

**5、Electronic Characteristics of Module :**

- |                              |                               |                                     |
|------------------------------|-------------------------------|-------------------------------------|
| 1. Input Voltage :           | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 2. Supply Current :          | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 3. Driving Voltage for LCD : | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 4. Contrast for LCD :        | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 5. B/L Driving Method :      | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 6. Negative Voltage Output : | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 7. Interface Function :      | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 8. LCD Uniformity :          | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 9. ESD test :                | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |
| 10. Others :                 | <input type="checkbox"/> Pass | <input type="checkbox"/> NG , _____ |

**6、Summary :**

Sales signature : \_\_\_\_\_

Customer Signature : \_\_\_\_\_

Date :     /     /

## **14.Initial code**

```
void initial()
{
    RES=1;
    Delay_ms(120);
    RES=0;
    Delay_ms(10);
    RES=1;
    Delay_ms(120);

    write_com(0xD7);    // Disable Auto Read
    write_dat(0x9F);

    write_com(0xE0);    // Enable OTP Read
    write_dat(0x00);
    Delay_ms(10);

    write_com(0xE3);    // OTP Up-Load
    Delay_ms(20);

    write_com(0xE1);    // OTP Control Out

    write_com(0x11);    // Sleep Out

    write_com(0x28);    // Display OFF
    Delay_ms(50);

    write_com(0xC0);    // Set Vop
    write_dat(0xA1);    //
    write_dat(0x00);    //

    write_com(0xC3);    // BIAS System
    write_dat(0x05);    //

    write_com(0xC4);    // Booster Level
    write_dat(0x05);

    write_com(0xD0);    // Enable Analog Circuit
    write_dat(0x1D);

    write_com(0xB5);    // N-Line Inversion
    write_dat(0x00);    //

    write_com(0x39);    // Display Mode

    write_com(0xF1);    // Frame Rate (Monochrome Mode)
    write_dat(0x06);    //
    write_dat(0x0B);    //
```

```

write_dat(0x0D);    //
write_dat(0x10);    //

write_com(0x3A);    // Enable DDRAM Interface
write_dat(0x02);

    write_com(0x36);    // Display Control
write_dat(0xC8);    //

write_com(0xB0);    // Display Duty
write_dat(0x3F);    //

write_com(0x20);    // Inverse Display

write_com(0x37);    // Start Line
write_dat(0x00);    //

write_com(0xB1);    // First Output COM
write_dat(0x00);    //

write_com(0xB3);    // FOSC Divider
write_dat(0x00);

write_com(0x2A);    // Set Column Address
write_dat(0x00);    //
write_dat(48);        //
write_dat(0x00);    //
write_dat(127);        //

write_com(0x2B);    // Set Row Address
write_dat(0x00);    //
write_dat(96);        //
write_dat(0x00);    //
write_dat(159);        //

write_com(0xC4);    // Booster Level
write_dat(0x07);

write_com(0x29);    // Display ON
}

```