

AMY-50-RS-C

~15° spot beam with tight cutoff. Assembly with holder C compatible with LEDiL HEKLA. Black version.

SPECIFICATION:

Dimensions	Ø 49.9 mm
Height	13 mm
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish
AMY-50-RS	Single lens	PMMA	clear	
AMY-50-HLD-C	Holder	PC	black	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CP18643_AMY-50-RS-C » Box size: 480 x 280 x 300 mm	510	120	30	9.1





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):


CITIZEN

LED CLL02x/CLU02x (LES10)
FWHM / FWTM 17.0° / 31.0°
Efficiency 85 %
Peak intensity 5.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17435_HEKLA-G2-C



CITIZEN


LED CLU700/701/702/703
FWHM / FWTM 11.0° / 19.0°
Efficiency 87 %
Peak intensity 11.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17435_HEKLA-G2-C




OPTICAL RESULTS (SIMULATED):




LED V3 HD Gen 8
FWHM / FWTM 8.0° / 15.0 + 16.0°
Efficiency 89 %
Peak intensity 20.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15253_HEKLA-SOCKET-A




LED V4 HD Gen 7
FWHM / FWTM 8.0° / 16.0°
Efficiency 87 %
Peak intensity 19.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15253_HEKLA-SOCKET-A



LED V4 HD Gen 8
FWHM / FWTM 8.0° / 16.0°
Efficiency 87 %
Peak intensity 18.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15253_HEKLA-SOCKET-A




LED V6 HD Gen 7
FWHM / FWTM 10.0° / 20.0°
Efficiency 86 %
Peak intensity 12.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F15255_HEKLA-SOCKET-C



OPTICAL RESULTS (SIMULATED):




LED Vesta DTW 6mm
FWHM / FWTM 12.0° / 22.0°
Efficiency 88 %
Peak intensity 9.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
Bender Wirth: 652b Hekla




CITIZEN

LED CLL03x/CLU03x
FWHM / FWTM 26.0° / 49.0°
Efficiency 83 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




CITIZEN

LED CLU7B2
FWHM / FWTM 8.0° / 14.0°
Efficiency 84 %
Peak intensity 21.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
F17435_HEKLA-G2-C




LED CMA1516
FWHM / FWTM 15.0° / 29.0°
Efficiency 86 %
Peak intensity 6.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OPTICAL RESULTS (SIMULATED):



LED COB S-Type (LES 7)
 FWHM / FWTM 12.0° / 22.0°
 Efficiency 84 %
 Peak intensity 9.6 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:
 Bender Wirth: 652a Hekla



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)